

## 1: PRODUCT AND COMPANY IDENTIFICATION

Product Name: **Digermane (Ge<sub>2</sub>H<sub>6</sub>)**  
IUPAC Name: Digermanium hexahydride  
Other Product Names: Germanium hydride, germanium (III) hydride, germanium trihydride.

Manufacturer: **Metaloid Precursors, Inc.**  
226 Metro Drive, Metrocrest Industrial Park  
Terrell, TX 75160-9169  
United States of America  
<http://www.metaloids.com>

**Basic Description:** Toxic Liquid, Flammable, n.o.s. (Digermane), Division 6.1 (Toxic Liquid, Flammable Liquid), UN

2929. Toxic - Inhalation Hazard, Inhalation Hazard Zone B.

**Additional Information for shipment by water:** IMDG Page Number 6220-3.

Telephone Number: 1-972-563-2010  
Facsimile: 1-972-692-5486

Hazard Class: 6.1 (toxic, flammable liquid).  
Code Number: UN 2929  
Date Prepared: June, 2007.  
CAS: 13818-89-8  
Chemical Family: Liquid, toxic, flammable.  
Product Class: Saturated liquid  
D.O.T. Label: Poison, flammable liquid.  
NFPA 704: Health 4, Fire 4, Reactivity 3, Other unspecified.  
HMIS code: Health 4, Fire 4, Physical Hazard 3.

Product Use: Digermane is a dense source of germanium atoms, for depositing germanium thin films and amorphous germanium-silicon alloy hetero-structures used in electronic device manufacturing.

## 2: COMPOSITION/INFORMATION ON INGREDIENTS

INGREDIENT	OSHA PEL <sup>†</sup>	ACGIH TLV <sup>†</sup>
Digermane – 100%	0.2ppm for 8h TWA	0.2ppm

<sup>†</sup> Digermane is structurally close to germane and is a by-product in germane production. Permissible exposure limit (PEL) and threshold limit value (TLV) are based on germane gas for which toxicological data is available.

## 3: HAZARDS IDENTIFICATION

### 3.1 Emergency overview

For emergency assistance (accident, fire, exposure, or leak), contact CHEMTREC 1-800-424-9300

Color None	Flammable Yes	Toxic/Poison Gas Yes	Odor Pungent	Heavier than air at stp Yes
---------------	------------------	-------------------------	-----------------	--------------------------------

Digermane is a toxic gas. Digermane decomposes at around 300°C into germanium metal dust and hydrogen gas while releasing thermal energy (162 kJ/mol suggested by bond energies).

### 3.2 Health effects

Inhalation Hazard Yes	Respiratory Irritant Yes	Exposure Limits Yes	Eye Irritant None known	Skin Irritant None known
Teratogen None known	Mutagen None known	Carcinogen None known	Ingestion Hazard None known	Cryogenic effects Liquid burns skin

Health hazards resulting from germanium hydride poisoning include, but are not limited to, hemolysis (breaking open of red blood cells and the release of hemoglobin into the surrounding fluid), and renal or kidney tissue damage.

Primary route of entry:	Inhalation of digermane contaminated air.
Effects of acute exposure:	General malaise, including headache, breathing problems, nausea, tightness in the chest and abdominal pain. Depending on dosage of inhaled gas, acute exposure can result in unconsciousness and possible death.
Effects of chronic exposure:	Kidney damage, possible death

### 3.3 Flammability

<b>Flammability Classification</b>	<b>Flammable</b>
Flash Point	Not available.
Auto ignition temperature	Not available.
Flammable Limits in Air	None established. Assume 100% at upper limit

## 4. First Aid Measures

<b>Inhalation</b>	<p>This is the primary route of exposure to poisonous gases. Do not enter a confined space containing digermane-contaminated air unless you are equipped with a portable and self-contained breathing apparatus.</p> <p>(a) If safe, immediately remove the casualty from contaminated area into fresh air.</p> <p>(b) If casualty is unresponsive, open his/her airway by tilting head and lifting chin at the same time.</p> <p>(c) Look, listen and feel for signs of breathing and pulse. If breathing is compromised, administer cardiopulmonary resuscitation (CPR) with two initial breaths. Each breath should make the chest rise.</p>
-------------------	-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

For emergency assistance (accident, fire, exposure, or leak), contact CHEMTREC 1-800-424-9300

	<p>(d) If there is no pulse, administer 15 chest compressions for every CPR breath.</p> <p>(e) Place casualty in recovery position to prevent tongue from blocking the throat and allow liquids to drain easily from the mouth. In the recovery position, the head, neck and back should be kept aligned, while the bent limbs keep the body propped comfortably and securely.</p> <p>(f) Call an emergency ambulance (911 in US/Canada, 999 in UK).</p> <p>(g) Keep casualty warm, comfortable, and at rest while awaiting professional medical care. <i>Monitor breathing and pulse every 10 minutes while waiting for medical assistance to arrive.</i> Administer CPR and chest compressions if needed.</p>
<b>Skin Contact</b>	<p>Digermene is gaseous at room conditions. Although intimate skin contact is unlikely under safe operating conditions, a defective valve can throw a gaseous plume onto personnel, in which case, clothing can become saturated in digermene leading to prolonged skin contact. First aid measures include:-</p> <p>(a) Quickly move away from source of contamination to fresh air</p> <p>(b) Immediately remove contaminated clothing.</p> <p>(c) Assume gas has been inhaled and call for assistance. Call an emergency ambulance (911 in US/Canada, 999 in UK).</p>
<b>Eye Contact</b>	<p>(a) Flush eye several times with clean cold water ensuring the water drains away from the eye.</p> <p>(b) Do not touch or rub the eye.</p> <p>(c) Refrain from looking around to avoid moving eye-ball.</p> <p>(d) Place sterile dressing or clean pad over eye and keep uninjured eye closed.</p> <p>(e) Call an emergency ambulance (911 in US/Canada, 999 in UK).</p>
<b>Ingestion</b>	<p>Although exposure by ingestion is not common, however under such circumstances immediately call an emergency ambulance.</p>

## 5. Fire Fighting Measures

Conditions of flammability	Ignition source and oxidant present.
Exinction	Immediately evacuate all personnel and isolate scene as a hazard area. If safe to do so shut off digermene gas supply, otherwise allow fire to consume the gas completely.

For emergency assistance (accident, fire, exposure, or leak), contact CHEMTREC 1-800-424-9300

	<p>Allowing gas to burn avoids the formation of a toxic and explosive mixture in air. If fire is proximal to gas cylinder, spray cylinder and surrounding area with cold water to dissipate heat of combustion and prevent dangerous pressure buildup and possible mechanical weakening of cylinder and its valve.</p> <p>Use a positive pressure, self contained breathing apparatus with a full face-piece that meets industry standards in all fire fighting involving digermane gas.</p>
Upper flammable limit	Assume 100%
Lower flammable limit	Not established.
Hazardous combustion products	Germanium hydride burns to form germanium oxide particulates which present an inhalation (dust) hazard.
Explosion data	None established.

## 6. Accidental Release Measures

In a digermane gas release in an unconfined space (e.g. outside storage area), immediately evacuate all personnel to a location up-wind of leakage source. Because digermane gas is heavier than air at room conditions, gas leakage can diffuse at ground level for hundreds of feet. The footprint depends on quantity of digermane released, ambient wind speed, temperature and nature of terrain. Evacuated personnel should avoid ignition sources, e.g. lit cigarettes.

Where a leak occurs in a confined space such as in a laboratory setting, or in a fume hood or gas cabinet, the user should purge the contaminated space thoroughly with a non-reactive gas such as nitrogen. Air in the contaminated space should be tested for residual digermane gas. The affected space should not be considered safe until the air has been tested and demonstrated to contain at least 19.5% oxygen. Personnel should strictly observe safety procedures which include wearing a full body suit and breathing equipment with a full-face mask attached to a portable air pack or airline.

### Containment

Digermane gas should be stored at room temperature in a sealed cylinder in compliance with CGA P-1, *Safe Handling of Compressed Gases in Containers*, local ordinances and applicable regulations. If gas cylinder is connected to a piping system fed by other fluids from high pressure sources, the piping design and operation should prevent possible back flow of process or non-process fluids into the digermane gas cylinder. Should back-flow occur and the digermane cylinder becomes contaminated, user should immediately contact vendor.

## 7. Handling and Storage

Health hazard from digermane gas inhalation can occur at 0.2ppm. Small digermane gas leaks can spread rapidly in air currents generated by room fans and vehicle motion. Any small leak presents a potential health risk and must be appropriately managed (see Section 6).

### Handling Procedures and Safety Considerations

Facilities using digermene gas are advised to install emergency oxygen equipment, safety showers and eyewash fountains. Additionally, an emergency response plan and personnel trained on emergency procedures are recommended. Strictly, there should be NO open flames, NO sparks and NO smoking.

Operations should be conducted in facilities suitably designed to handle hazardous gases safely and should comply with industry guidelines (see *CGA P-1, Safe Handling of Compressed Gases in Containers*), local ordinances and applicable regulations. Users are hereby recommended to consult specialists on hazardous gaseous material for the design and operation of gas handling systems. Key safety components include:-

### **Codes and Standards**

ATEX, NEC and other national/regional codes. Non-sparking equipment and earth bonding of equipment are recommended. Electrical equipment should be explosion proof or rendered safe by appropriate shrouding and continuous purging of shrouds with non reactive gases such as nitrogen.

### **Enclosed Spaces**

Should be provided with inert purge gases such as helium or nitrogen. Enclosures should advantageously have vent line sensors and aerial detectors in adjacent work areas, all hard wired to facility alarms. Use of Hydrogen deflagration Nomograph for venting is recommended (see NFPA document 68 "Venting of Deflagrations").

### **Removing Valve Dust Caps**

A bubble of digermene gas can buildup behind the outlet dust cap during transportation, after prolonged storage, due to defective cylinder valve or if dust cap is inserted without adequate evacuation of digermene gas from line. When loosening dust cap, preferably stand cylinder in a suitable enclosure under negative pressure (relative to atmospheric pressure) and take off cap slowly. Never face the dust cap directly when removing it and point cap away from any personnel or any object that may pose a hazard.

### **Connecting and Disconnecting Digermene Gas Cylinders**

The tubing network design connecting digermene gas cylinders to your system should include appropriate pressure indicators, inert gas supply and vacuum or suction lines. Fully-welded types of pressure gauges where the bourdon tube sensing element is welded to gage body are recommended. Before connecting digermene gas cylinder, ensure the manifold is mechanically secure and does not contain an oxidizing gas. Before disconnecting digermene gas cylinder, isolate supply line segment proximal to cylinder, remove trapped digermene gas in supply line with the aid of a vacuum pump and back-fill it with helium or nitrogen. Never introduce any substance into a digermene gas cylinder. If your gas cylinder is contaminated then notify gas manufacturer or vendor immediately.

### **Storage Cylinder Handling**

Digermene gas cylinders should be stored and maintained in accordance with CGA P-1, *Safe Handling of Compressed Gases in Containers*, and in compliance with State and Federal Laws, including building and fire codes. Digermene cylinders should be stored upright, firmly secured in a cool, dry, well-ventilated area and away from heavily used access routes and emergency exits.

For emergency assistance (accident, fire, exposure, or leak), contact CHEMTREC 1-800-424-9300

Storage room temperatures should not exceed 50°C (122°F). All cylinders, full or empty, should be fitted with dust caps. Do not store close to oxidizers and halogens.

### Cylinder Handling

Use a suitable hand truck to move cylinders. Do not drag, roll, slide or drop. Never attempt to lift a cylinder by its cap. Cylinder cap is intended to protect valve. Never insert pointed objects (e.g., hooks) into cylinder cap openings as a means to open cap or move cylinder. Such action can inadvertently turn the valve and cause a toxic gas leak. Use an adjustable strap instead of a wrench to free an over-tight or rusted cap. Open valve slowly. If valve is resistant to opening then contact your supervisor.

## 8. Exposure Controls/Personal Protection

### Specific engineering controls to be used

Also see Section 7. To minimize the risk of personnel exposure to digermene gas, the cylinders should be kept in a hazard gas cabinet or dedicated storage area fitted with leak detectors. When carrying out routine work, such as changing digermene gas cylinders, operator should stand outside enclosure where possible, carry a portable leak detector or wear a respiratory protection system to go inside enclosure.

### Personal protective equipment to be used

<b>Inhalation hazard</b>	Use full face positive-pressure mask on an air line or a portable self-contained breathing apparatus equipped with an escape air capsule in response to a leak.
<b>Eye/Face Protection</b>	Use safety goggles or glasses to guard against accidental gas jet-impact.
<b>Skin Protection</b>	Use industry standard gloves for fire protection.
<b>Slip</b>	Use industry standard non-slip and anti-static shoes.

## 9. Physical and Chemical Properties

Physical state at room conditions	Gas
Vapor Pressure:	10.7 psia at 21°C
Auto-ignition Temperature	None established.
Boiling Point	31.5°C at 14.696 psia.
Vapor Density	6.22 g/L at 0°C
Melting/Freezing Point	-109°C
Molecular Weight	151.328
Water Solubility	Insoluble
Odor	Pungent
Appearance	Colorless

### Note to Users:

Digermene gas is 5.2 times heavier than air, can travel along the ground to a remote ignition point and fuel a vapor cloud explosion.

## 10. Stability and Reactivity

<b>Chemical stability</b>	Liquid not stable at room temperature. Can decompose exothermically into germanium metal and hydrogen gas.
<b>Incompatibility with</b>	Halogens and oxidizers
<b>Decomposition in air</b>	Hydrogen, germanium oxide
<b>Hazardous polymerization</b>	Not known

## 11. Toxicological Information

Data on digermane toxicology not known to Metaloid Precursors, Inc. For the primary hydride germane, the respiratory LC<sub>50</sub> in mice is 1380 mg/m<sup>3</sup>. In this study, clinical signs were dyspnea, convulsion and coma. Autopsy revealed congested internal organs, hemorrhages, nerve cell vacuolization and degenerative changes in the cells of parenchymal organs. Guinea pigs exposed to 80 – 480ppm germanium hydride revealed similar pathological changes.

## 12. Ecological Information

None known.

## 13. Disposal Considerations

Disposal of unused quantities in air is strongly discouraged. Waste gas can be burned in an approved incinerator equipped with an afterburner and scrubber. Users can, with written approval, return in the original shipping cylinder any unused quantities with labels, valve plugs, cylinder cap in place and a post-sale certificate of analysis to Metaloid Precursors, Inc. for disposal.

**Classification under RCRA, 40 CFR 261:** Material meets criteria for an "acute hazardous waste".  
**US EPA waste number and descriptions:** D001 (ignitability) and D003 (reactivity).

## 14. Transport Information

### U.S. DOT 49 CFR 172.101:

PROPER SHIPPING NAME: Digermane; ID NUMBER: UN 2929  
HAZARD CLASS OR DIVISION: 6.1; LABELING REQUIREMENTS: 6.1  
PASSENGER AIRCRAFT: Forbidden; CARGO AIRCRAFT ONLY: Forbidden  
RAILCAR: Forbidden; CAR/STATION WAGON: Forbidden  
ADDITIONAL SHIPPING DESCRIPTION: Toxic-Inhalation Hazard Zone B  
PARKING GROUP: I

### CANADIAN TRANSPORTATION OF DANGEROUS GOODS:

SHIPPING NAME: Digermane; UN NUMBER: UN2929;  
CLASS: 6.1

## 15. Regulatory Information

**Toxic Substances Control Act (TSCA):** Digermene is a “by-product” (40 CFR 730.3 (d)) in a commercial process and its supply to end-user is restricted by TSCA to research and development purposes (40 CFR 730.3 (cc) and 40 CFR 730.36) under the supervision of a “technically qualified individual” (40 CFR 730.3 (ee)). The sourcing or acquisition of digermene for “commercial purposes” as defined by 40 CFR 730.3 (r) is disallowed in the United States. Similar restrictions may apply in other countries.

**CERCLA Reportable Quantity (40 CFR 302.40):** This material is not listed. The Reportable Quantity (RQ) for “Unlisted Hazardous Wastes Characteristic of Ignitability” (D001) or “Unlisted Hazardous Wastes Characteristic of Reactivity” (D003) of 45.4 kg (100 lbs.) therefore applies.

**SARA Title III Status (Section 302 (40 CFR 355), Section 311/312, Section 313 (40CFR372)):** No Threshold Planning Quantity (TPQ) or Reportable Quantity (RQ) is listed for this substance. The default federal MSDS submission and inventory requirement filing threshold of 4,540 kg (10,000 lbs.) therefore applies.

**SARA Title III Hazard Classes:** Acute health hazard, chronic health hazard, fire hazard, sudden release of pressure hazard

**Other:** Obtain written permission from owner before refilling a compressed gas cylinder. It is a violation of transportation regulations to transport a compressed gas cylinder that has not been filled by the owner or without written permission.

## 16. Other Information

### REFERENCES

ANSI Standard Z400.1-1993

§ 29 CFR 1910, Subpart Z, revised July 1993

† *American Conference of Government Industrial Hygienists*, 2006 Threshold Limit Values and Biological Exposure Indices.

Health Council of the Netherlands, Report No. 2000/150SH/006, The Hague, 14 December 2000.

Saul Patai, *The Chemistry of Organic Germanium, Tin and Lead Compounds*, 1995 John Wiley & Sons, Ltd.

Butterman W.C. et al, Germanium, Open-File Report 2004-1218, U.S. Geological Survey, Reston, Virginia 2005

For emergency assistance (accident, fire, exposure, or leak), contact CHEMTREC 1-800-424-9300

Karen Craig and Loraine Hopkins-Pepe, American Heart Association Guidelines, part 1; Nursing 2006, Vol. 36, Number 4, p53.

E. Browning, *Toxicity of Industrial Metals*, Appleton-Century-Crofts, New York, 2<sup>nd</sup> Edition, 1969, pp 162-163.

*US Department of Labor, Occupational Safety and Health Administration, 1993.*

*Kenneth Book of SEMI Standards, Facilities Standards and Safety Guidelines*. Mountain View, CA, Semiconductor Equipment and Materials International, 1993.

*Safe Handling of Compressed Gases in Containers* (Pamphlet P-1). Arlington, VA: Compressed Gas Association, Inc., 1991.

Swennen B. et al, *Epidemiological survey of workers exposed to inorganic germanium compounds*, *Occup. Environ. Med.*, vol. 57, 2000, pp242-248.

**DISCLAIMER OF EXPRESSED AND IMPLIED WARRANTIES**

INFORMATION IN THIS MSDS IS BASED ON TECHNICAL DATA, WHICH METALOID PRECURSORS, INC., dba "METALLOIDS" BELIEVES TO BE RELIABLE. HOWEVER, THE CONDITIONS UNDER WHICH THIS INFORMATION MAY BE APPLIED VARY AND ARE BEYOND THE CONTROL OF METALLOIDS. THE MANUFACTURER THEREFORE ASSUMES NO LIABILITY WHATSOEVER FOR RESULTS OF ITS APPLICATION. USERS ARE EXCLUSIVELY RESPONSIBLE AND ACCOUNTABLE FOR THE PROPER STORAGE, HANDLING, USE AND DISPOSAL OF THIS PRODUCT, AND FOR OBSERVING STATUTES, REGULATIONS, ORDINANCES AND INDUSTRY BEST PRACTICES. ONLY PERSONS HAVING SUFFICIENT SKILL TO MAKE INFORMED JUDGMENTS REGARDING PRODUCT APPLICATION SHOULD USE THIS INFORMATION.